

# CPI 2.25 kW SuperLinear™ TWT Amplifier for Satellite Communications

C-Band

## The TL22CI

2.25 kW (1000 W operating) TWT Compact High Power Amplifier, features high efficiency, small size and integral computer interface.



### Compact

Provides 2250 watts of peak power (1000 watts operating) in a compact nine rack-unit package, digital ready, for wideband, single- and multi-carrier satellite service in the 5.85 - 6.65 GHz frequency band. Designed to operate at 1000 watts flange linear power for multi-carrier uplinks. Ideal for transportable and fixed earth station applications where space and prime power are at a premium. 30% smaller than traditional HPAs.

### Efficient and Reliable

Employs an ultra-high efficiency dual-depressed collector helix traveling wave tube backed by many years of field-proven experience in airborne and military applications. The collector design is optimized for super-cool operation.

### Simple to Operate

User-friendly microprocessor-controlled logic with integrated computer interface, digital metering, pin diode attenuation, optional integrated linearizer for improved intermodulation performance, and BUC option for use with C-band modems.

### Global Applications

Meets International Safety Standard EN-60215 and EMC Standard 2004/108/EC to satisfy worldwide requirements.

### Easy to Maintain

Modular design and built-in fault diagnostic capability with convenient and clearly visible indicators for easy maintainability in the field.

### Worldwide Support

Backed by over two decades of satellite communications experience, and CPI's worldwide 24-hour customer support network that includes sixteen regional factory Service Centers.

**satcom**  **division**

811 Hansen Way  
P.O. Box 51625, Palo Alto, CA 94303

**tel:** +1 (650) 846-3803  
**fax:** +1 (650) 424-1744

**e-mail:** [marketing@satcom.cpii.com](mailto:marketing@satcom.cpii.com)  
[www.cpii.com/satcom](http://www.cpii.com/satcom)

C-Band

2.25 kW SuperLinear™ Compact TWTA

## OPTIONS & COMPANION PRODUCTS:

- *Integral Linearizer*
- *Remote Control Panel*
- *Redundant and Power Combined Subsystems*
- *Extended Frequency (5.850 - 6.725 GHz or 5.725 - 6.525 GHz)*
- *External Receive Band Reject Filter*
- *Integral L-Band Block Upconverter (BUC)*

## SPECIFICATIONS, TL22CI

### Electrical

Frequency	5.85 - 6.65 GHz
Output Power	
TWT	2250 W min. (63.54 dBm)
Flange	1000 W max operating. (60.00 dBm)
Bandwidth	800 MHz (1225 MHz optional)
Gain	75 dB min. at rated power output 78 dB min. at small signal
RF Level Adjust	0 to 30 dB continuous
Output Power Adjustability	±0.1 dB
Gain Stability	±0.25 dB/24 hr max. (at constant drive and temp.)
Small Signal Gain Slope	0.02 dB/MHz max.
Small Signal Gain Variation	0.5 dB pk-pk max. over any 40 MHz; 1.0 dB pk-pk max. over any 40MHz with linearizer option; 3.0 dB pk-pk max. across 800 MHz; 4.0 dB pk-pk max. across 800 MHz with linearizer option; 5.0 dB pk-pk max. across 800 MHz with BUC option; 6.0 dB pk-pk max. across 800 MHz with BUC and linearizer options
Input/Output VSWR	1.25:1 max.
Load VSWR	2.0:1 max. for full spec compliance; any value without damage
Residual AM, max. <sup>1</sup>	-50 dBc below 10 kHz, -20 (1.5 + log F kHz) dBc, 10 kHz to 500 kHz (F in kHz) -85 dBc above 500 kHz
Phase Noise <sup>1</sup>	
IESS-308/309	
phase noise continuous	10 dB below mask at -10 dB backoff
AC fundamentals related	-50 dBc
Sum of spurs	-47 dBc
AM/PM Conversion	6°/dB max. With optional linearizer, can be tuned to 2°/dB max.
Harmonic Output	-80 dBc
Noise and Spurious	-150 dBW/4 kHz from 3.4 to 4.2 GHz -65 dBW/4 kHz from 4.2 to 12.0 GHz -60 dBW/4 kHz from 4.2 to 12.0 GHz with linearizer option -110 dBW/4 kHz from 12.0 to 40.0 GHz
Intermodulation	
with two equal carriers	-23.5 dBc max, 5.850 - 6.425 GHz at 400 W without linearizer (-25 dBc max. at 890 W with linearizer); -22 dBc max. 6.425 - 6.650 GHz at 400 W without linearizer (-24 dBc max. at 890 W with linearizer)

### Electrical (continued)

Group Delay	0.01 ns/MHz linear (in any 40 MHz band) 0.001 ns/MHz <sup>2</sup> parabolic 0.5 ns pk-pk ripple max.
Primary Power <sup>2</sup>	All ratings are ±10%, 47-63 Hz, 5-wire, 3-phase with neutral and ground 200 to 240 VAC (with or w/o neutral) 380 to 415 VAC
Power Factor	0.95 min.
Power Consumption	5.0 kW max.; 4.5 kW typ. @ 1000 W linear RF output power; 3.8 kW typ. @ 800 W; 3.5 kW typ. @ 600 W; 3.3 kW typ. @ 400 W; 2.9 kW typ. @ 200 W; 2.5 kW typ. @ 100 W

### Environmental

Ambient Temperature	-10° to +50°C operating -20° to +70°C non-operating
Relative Humidity	95% non-condensing
Altitude	Up to 10,000 ft (3000 m) with standard adiabatic derating of 2°/1000 ft.; 50,000 feet non-operating
Shock and Vibration	Designed for normal transportation environment per Section 514.4 MIL-STD-810E. Designed to withstand 20g at 11 ms (1/2 sine pulse) in non-operating condition

### Mechanical

Cooling(TWT)	Forced air with integral blower and power supply fan. Maximum external pressure loss allowable: 0.25 inch water gauge.
RF Input Connection	Type N female
RF Output Connection	CPR 137 F waveguide flange, grooved, threaded UNF 2B 10-32
RF Power Monitors	Type N female
Dimensions (W x H x D)	19 x 15.75 x 24 in. (483 x 400 x 610 mm)
Weight	155 lbs. (70.5 kg) max.

<sup>1</sup>Prime power AC line unbalance not to exceed 3%. Excess imbalance may cause an increase in residual RF noise (AM, FM and PM). Phase noise increase is typically 2.5 dB / % imbalance.

<sup>2</sup>AC current harmonic content: less than 20%, primarily fifth and seventh harmonics. Harmonics must be considered when choosing UPS sources.



Communications & Power Industries

satcom division

For more detailed information, please refer to the corresponding CPI Technical Description.

Note: Specifications may change without notice as a result of additional data or product refinement.

Please contact CPI before using this information for system design.