

3000C Controller



TECHNICAL SPECIFICATIONS



The new iNetVu 3000C hand-held manual controller has the same look and feel as a video game controller. It allows you to operate the platform without having the auto-pointing controller or PC attached to it. In addition, this controller makes it possible to operate the iNetVu mobile antenna at variable speeds.

A useful tool for conducting demonstrations, installations, testing or for emergency backup situations.

Features

- Jog control on 3 axis
- Compatible with all iNetVu Mobile Platforms
- Ability to raise, stow, and move the iNetVu Mobile Platform during demos, installations, trouble-shooting etc.
- Compact, ergonomic case design
- LCD display for operation and limits status
- 10-speed operation
- Directly attachable to any 12VDC power supply
- Enhanced operation with feedback control

Electrical

| | |
|-------------|----------------------------|
| Power Input | 12 VDC @ 15Amp max. |
| Motor | 9 pin, 15 ft cable. |
| Sensor | DB-26, 15 ft sensor cable. |

Environmental

| | |
|-----------------------|------------------|
| Operating temperature | -20° C to +60° C |
| Storage temperature | -40° C to +70° C |
| Standard | RoHS compliant |

Mechanical

| | |
|------------|--------------------------|
| Dimensions | 7" (W) x 5" (H) x 2" (D) |
| Weight | 500 gm |

Standard Warranty: 2 years

Please Note:

Motor and sensor cables are compatible with 7000 controller

www.c-comsat.com
(613) 745-4110 (877) 463-8886



Specifications are subject to change

Sept. 2011