

1.8 m Type-Approved Tx/Rx Antenna Systems

Intelsat Type-Approval #IA091A00
Eutelsat Type-Approved

C-Band		C-Band Linear	
Polarity		Receive	Transmit
Frequency		3.4-4.2 GHz	5.7-6.725 GHz
Feed - 2 Port Xpol			
Return Loss		17.7 dB typ	17.7 dB
Insertion Loss		0.2 dB	0.2 dB
Tx/Rx Isolation		40 dB	70 dB
Feed Interface		WR229	WR137
Antenna Specifications			
Efficiency		70%	70%
Midband Gain		36.0 dBi	39.8 dBi
Noise Temperature		55 K @ 10°	---
	(6.138 Tx, 4.0 Rx)	50 K @ 30°	
Cross Pol On Axis		30 dB	30 dB
	1 dB beamwidth	22 dB	25 dB
Tx/Rx Sidelobe Level		29 - 25 log θ	
		-3.5	
		32 - 25 log θ	
		-10	

C-Band Circular			
Polarity		Receive	Transmit
Frequency		3.625-4.2 GHz	5.85-6.425 GHz
Feed - 2 Port Xpol			
Return Loss		17.7 dB typ	17.7 dB
Insertion Loss		0.3 dB	0.2 dB
Tx/Rx Isolation		40 dB	60 dB
Feed Interface		WR229	WR137
Antenna Specifications			
Efficiency		70%	70%
Midband Gain		35.6 dBi	39.5 dBi
Noise Temperature		65K @ 10°	---
	(6.138 Tx, 4.0 Rx)	60K @ 30°	
Cross Pol On Axis		15.3 dB	17.7 dB
	1 dB beamwidth	15.3 dB	17.7 dB
Tx/Rx Sidelobe Level		100 $\lambda/D < \theta < 20^\circ$	
		20° < θ < 26.3°	
		26.3° < θ < 48°	
		48° < θ	

Ku-Band		Ku-Band Linear	
Polarity		Receive	Transmit
Single Optic Frequency		10.7 - 12.75 GHz	13.75-14.5 GHz
Feed - 2 Port Xpol			
Return Loss		17.7 dB typ	20 dBtyp
Insertion Loss		0.3 dB typ	0.1 dBtyp
Tx/Rx Isolation		40 dB	80 dB
Feed Interface		WR75	WR75
Antenna Specifications			
Efficiency		70%	70%
Midband Gain		45.3 dBi	47.0 dBi
Noise Temperature		55 K @ 10° EL	---
		50 K @ 30° EL	---
Cross Polarization On Axis		30 dB	30 dB
within 1 dB Beamwidth		22 dB	26 dB
Tx/Rx Sidelobe		100 $\lambda/D < \theta < 20^\circ$	29 - 25 log θ
		20° < θ < 26.3°	-3.5
		26.3° < θ < 48°	32 - 25 log θ
		48° < θ	-10

X-Band		X-Band Circular	
Polarity		Receive	Transmit
Frequency		7.25 - 7.75 GHz	7.9 - 8.4 GHz
Feed - 2 Port Xpol			
Return Loss		17.7 dB typ	17.7dB
Insertion Loss		0.3 dB typ	0.2 dB typ
*Tx/Rx Isolation		30 dB	30 dB
Feed Interface		WR112	WR112
Antenna Specifications			
Efficiency		70%	70%
Midband Gain		41.5 dBi	42.2 dBi
Noise Temperature		38 K @ 10°	---
		35 K @ 30°	
Cross Polarization On Axis		23 dB	21dB
1 dB beamwidth		23 dB	21 dB
Tx/Rx Sidelobe Level		100 $\lambda/D < \theta < 20^\circ$	29 - 25 log θ
		20° < θ < 26.3°	-3.5
		26.3° < θ < 48°	32 - 25 log θ
		48° < θ	-10

Eutelsat Type-Approved Specs			
Cross Polarization On Axis		35 dB	35 dB typ
within 1 dB Beamwidth		35 dB	35 dB typ
Tx/Rx Sidelobe		29 - 25 log θ	2.5° < θ < 7°
Level		8	7° < θ < 9.2°
		32 - 25 log θ	9.2° < θ < 48°
		-10	48° < θ

Mechanical Data	
f/D Ratio	0.61
Focal Distance	43.2 in / 109.7 cm
Mount Type	Elevation over Azimuth
Mast Pipe Size	4 in / 10.16 cm O.D.
Offset Angle	22°
Elevation Adjustment	8° to 90° Continuous Fine Adjustment
Azimuth Adjustment	+ 15° Fine, 360° Continuous

Environmental Data			
Wind Loading			
	Operational	60 mph, gusts of 80mph	101 kph, gusts to 130 kph
	Survival	120 mph	194 kph
125mph Wind forces			
	Wind Force	1,660 lbs	
	Overturning Moment	11,000 ftlb (on 60in ground pole)	
Temperature			
	Operational	-40° to 140° F	(-40° to 60°C)
	Survival	-60° to 180°F	(-51° to 82°C)
Rain			
	Operational	1.5 in/hr	(3.1 cm/h)
	Survival	3 in/ hr	(7.6 cm/h)
Ice			
	Survival	2.5cm (1 inch) radial or 1.3cm (.5 inch) radial+ 100 kph	

Patriot Antenna Systems
+1.517.629.5990 · 704 North Clark St. · Albion, MI 49224 USA
info@sepatriot.com · www.sepatriot.com · +1.517.629.6690 fax

12.8.05
© Copyright 2004 Patriot.
All product specifications subject to change without notice.

1.8 m Type-Approved Tx/Rx Antenna Systems



TX-INT180KU
Intelsat Type-Approval #IA083A00



TX-EUT180KU

Features

- AZ/EL interface to 4 in O.D. Pipe / 10.16 cm
- Azimuth Fine Tune $\pm 15^\circ$ for Pointing Accuracy
- Dual side galvanized steel powder coated
- Single Piece Deep Draw Reflector Provides Superior Surface
- Boom Supports 50 lbs / 22.26 kg
- Includes Two port Linear Tx/Rx Feed assembly

Description

Why pay more for a transmit/receive antenna? The Patriot single and dual optics antennas are excellent for VSAT applications and hold Intelsat type-approval. With a past history of use in high quality SNG (Satellite News Gathering) applications, the 1.8 m antenna provides a level of surface accuracy, rugged stiffness, and precision not often found in similarly priced products. The stamping process that produces the solid metal reflector results in superior surface accuracy and repeatability. The steel back structure adds strength and stability to the system and keeps the installation process simple.

The Navigator Style fine tune Azimuth and Elevation cap reduces pointing errors during installation, allowing more accurate boresighting on the satellite. Increased pointing accuracy leads to greater link availability. Special packaging techniques are employed for every system shipped to protect the surface of the dish.